

Site / Installation Details					
Client Name			Site Address		
Reference					
ALL BOXES NEED TO BE COMPLETED OR YOUR ORDER WILL BE DELAYED ALL VIEWS ARE FROM THE OUTSIDE please read our on-line guide to surveying before completing this form					
Position of Doors	Rear		Location Level	Ground	
	Side			First	
	Front			Other	
	Other				
Vehicle Access	Good		On Site Parking available	Yes	
	Bad			No	
Site Access	Good		On Site Storage Available	Yes	
	Bad			No	
Existing Frame to be removed by ClearSpan	Yes		Aperture Preparation	Client	
	No			ClearSpan	
Building Walls	Stone		External Finish	Bare	
	Brick			Render	
	Other			Other	
Internal finish	Bare		Plaster / Render Thickness	Left	
	Plaster			Right	
	Other			Head	
Images/sketches available					
Sizes					
Width Tight External		Width Tight Internal			
Height Tight External		Height Tight Internal			
External Diagonals (<i>top to bottom</i>)	Left		Frame Extensions Required	Head	
	Right			Left	
				Right	
Door Design			Door Options		
Configuration			Main RAL Colour		
Total Door Qty			Hardware Colour	Black	
Qty Doors opening to the Left				Chrome	
Qty Doors opening to the Right			Slot-Trickle Vents		
Direction of Opening (<i>Inward or Outward</i>)			Building control may require vents		
Threshold – Standard 75mm rebated			Threshold – Sheltered 55mm		
Sub-Cill required (<i>yes / no</i>)			There is no weather rating with 55mm threshold		
Sub-Cill type (<i>134mm / 190mm</i>)			i.e. possible water and wind ingress		
Glazing type 4mm Clear Toughened					
Glazing special description					
Overall Make WIDTH including extensions					
Overall Make Height including extensions					
Surveyors Signature			Date		
Contact No:-			Order Number		